

Encon[®]
SAFETY PRODUCTS

1-800-283-6266

Phone: (713) 466-1449 Fax: (713) 466-1703
E-Mail: customerservice@enconsafety.com

HORIZONTAL SHOWER

PART NUMBER: 01053001

SPECIFICATION:

Third party certified to ANSI Z358.1, the shower shall deliver 30 gpm (113.6 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Shower shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with 1 1/4" chrome plated (CP) bronze single motion activation stay open ball valve with CP ball, SS actuator with actuation graphic, schedule 80 hot dip galvanized steel piping and 1 1/4" supply connection. Shower head shall be supplied with self-adjusting 30 gpm (113.6 lpm) regulator to assure a constant flow and pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Shower head to be manufactured of UV resistant high visibility yellow ABS plastic. Shower head must deliver a minimum of 20" (50.8 cm) diameter pattern to the target area 60" (152.4 cm) above standing level. Shower units that provide improper flow pattern not acceptable. Shower unit shall be Encon Safety Products Model 01053001. For type 304 SS head, unit shall be Encon Safety Products Model 01053001SS. For all SS piping and valve, unit shall be Encon Safety Products Model 01053004.

MATERIALS OF CONSTRUCTION:

- PIPING:** Schedule 80 hot dip galvanized piping.
- VALVE:** 1 1/4" chrome plated bronze stay open ball valve with chrome plated ball, stainless steel valve stem and stainless pull rod assembly with actuation graphic.
- SHOWER HEAD:** Yellow ABS plastic shower head. Option: Type 304 stainless steel shower head.
- REGULATOR:** Self-adjusting 30 gpm (113.6 lpm) regulator.
- SUPPLY:** 1 1/4" NPT
- WEIGHT:** 11 lbs (4.98 kgs)

MODEL #	DESCRIPTION
01053001	As Specified
01053001SS	With SS shower head
01053004	With SS piping and valve
01053007	With SS shower head, piping and valve

