

SPECIFICATION:

Third party certified to ANSI Z358.1, the selfcontained gravity fed evewash shall deliver a noninjurious dual stream of water at a minimum volume of 0.4 gpm (1.5 lpm) for a full 15 minutes or longer. The eyewash heads are integral in an enclosed tray that provides protection against airborne contaminants when the eyewash is in a ready, non-activated state. When activated the pull down tray goes to a fixed, stay open position that allows full user access to the dual streams of fluid and channels spent fluids to a discharge port where an optional drain tray can be provided. Unit shall supply a minimum six gallons of useable flushing fluid stored in a yellow polyethylene tank that is noncorrosive by potable water. The highly visible eyewash incorporates front graphics to indicate activation method, maintenance and operational information. Two sturdy handles on the sides are included to assist when relocation of the unit is required. Eyewash shall be Encon Safety Products Model 01104050. When included with heavy-duty transport cart and fluid collection receptacle use model 01104055. For ABS drain tray assembly, order model 01110729 (in addition to Model 01104050).

MATERIALS OF CONSTRUCTION:

TANK: High visibility yellow polyethylene.
VALVE: Pinch hose valve.
HEAD: ABS plastic dual stream heads.
WATER TREATMENT ADDITIVE: 1 Bottle of Hydrosep® shipped with each unit. Treats 5 to 20 gallons (18.9 l to 75.7 l) up to 90 days.
WEIGHT: 15.2 lbs (6.9 kgs)

MODEL #	DESCRIPTION
01104050	Unit as Specified
01104055	With transport cart and fluid collection receptacle
01110729	Additional Drain Tray Assembly

SELF CONTAINED GRAVITY FED EYEWASH PART NUMBER: 01104050

