

# Encon®

SAFETY PRODUCTS

1-800-283-6266

phone: (713) 466-1449

email: customerservice@enconsafety.com

## EYEWASH WITH YELLO-BOWL® PART NUMBER: 01030301

### SPECIFICATION:

Third party certified to ANSI Z358.1, the eyewash shall deliver 3.2 gpm (12.1 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Eyewash shall provide a non-injurious stream of water for 15 minutes or. Unit shall be supplied with ½" chrome plated (CP) single motion activation stay open ball valve with CP ball. Eyewash shall include S/S actuator with actuation graphic, 7" X 11" (17.8 cm X 27.9 cm) sign and tailpiece. Unit must be supplied with self-adjusting 3.2 gpm (12.1 lpm) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Eyewash heads with hinged flip covers to be manufactured of UV resistant ABS plastic mounted in a high visibility ABS plastic Yello-Bowl®. Hinged flip covers are provided to inhibit dust and/or contamination when not in use. Eyewash units that provide improper flow pattern or contain deteriorating screens/filters are not acceptable.

Encon Safety Products Model 01030301 includes eyewash with Yello-Bowl®

**\*Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

### MATERIALS OF CONSTRUCTION:

**PIPING:** ½" Chrome plated brass.

**VALVES:** ½" Chrome plated bronze stay open ball valve with chrome plated ball, stainless steel valve stem and stainless steel push plate with actuation graphic.

**HEAD:** ABS plastic dual stream heads with hinged flip covers.

**BOWL:** High visibility ABS plastic Yello-Bowl®.

**REGULATOR:** Self-adjusting 3.2 gpm (12.1 lpm) regulator.

**SUPPLY:** ½" NPT

**WASTE:** 1¼" x 6" (3.17cm X 15.24cm) long slip joint tailpiece.

**WEIGHT:** 4 lbs (1.81 kgs)

