



# EYEWASH WITH YELLO-BOWL<sup>®</sup> WALL BRACKET, S/S PIPING AND S/S VALVE AND BALL UNIT PART NUMBER: 01030407

## SPECIFICATION:

Third party certified to ANSI Z358.1, the eyewash shall deliver 3.2 gpm (12.1 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Eyewash shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with ½” chrome plated (CP) single motion activation stay open ball valve with CP ball. Eyewash shall include S/S actuator with actuation graphic, 7” X 11” (17.8 cm X 27.9 cm) sign, tailpiece and wall mounting bracket. Unit must be supplied with self-adjusting 3.2 gpm (12.1 lpm) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Eyewash heads with hinged flip covers to be manufactured of UV resistant ABS plastic mounted in a high visibility ABS plastic Yello-Bowl<sup>®</sup>. Hinged flip covers are provided to inhibit dust and/or contamination when not in use. Eyewash units that provide improper flow pattern or contain deteriorating screens/filters are not acceptable.

**Encon Safety Products Model 01030401** includes eyewash with Yello-Bowl<sup>®</sup> and wall bracket.

**Encon Safety Products Model 01030403** includes eyewash with Yello-Bowl<sup>®</sup> w/ wall bracket and strainer tee.

**Encon Safety Products Model 01030407** includes eyewash with Yello-Bowl<sup>®</sup>, wall bracket and S/S piping with S/S valve and ball unit.

**\*Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

## MATERIALS OF CONSTRUCTION:

**PIPING:** ½” Chrome plated brass.

**VALVES:** ½” Chrome plated bronze stay open ball valve with chrome plated ball, stainless steel valve stem and stainless steel push plate with actuation graphic. Strainer Tee Option: ½” BCP, 16 mesh

**HEAD:** ABS plastic dual stream heads with hinged flip covers.

**REGULATOR:** Self-adjusting 3.2 gpm (12.1 lpm) regulator assures a constant and even dual stream flow pattern under varying hydraulic conditions.

**SUPPLY:** ½” NPT

**WASTE:** 1¼” x 6” (3.17cm X 15.24cm) long slip joint tailpiece.

**WEIGHT:** 6 lbs (2.72 kgs)

