

Encon[®]
SAFETY PRODUCTS
1-800-283-6266
 phone: (713) 466-1449
 email: customerservice@enconsafety.com

**30 GPM STAINLESS STEEL
 SHOWER HEAD**
PART NUMBER: 01055007

SPECIFICATION:

Shower head shall provide a non-injurious stream of water when mounted 96”(243.84cm) to 82”(208.28cm) from standing level. Shower head shall be supplied with self-adjusting 30 gpm (113.6 lpm) regulator to assure a constant flow and pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Shower head to be manufactured of type 304 stainless steel. Shower head shall deliver a minimum of 20”(50.8 cm) diameter pattern to the target area 60”(152.4 cm) above standing level. Shower units that provide improper flow pattern are not acceptable. **Encon Safety Products Model 01055005** includes 20 gpm shower head. **Encon Safety Products Model 01055007** includes 30 gpm shower head.

***Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

MATERIALS OF CONSTRUCTION:

SHOWERHEAD: Yellow ABS plastic shower head.

REGULATOR: Self-adjusting 30 gpm (113.6 lpm) regulator.

SUPPLY: 1” NPT

WEIGHT: 1 lbs (0.45 kgs)

