



SAF-T-LOK[®]
COUNTER-TOP EYEWASH
PART NUMBER: 01040124

SPECIFICATION:

Third party certified to ANSI Z358.1, the eyewash shall deliver 2.4 gpm (9.1 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Unit shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with ½” chrome plated (CP) single motion activation stay open ball valve with CP ball. Unit shall include left-hand countertop mounted actuator with actuation graphic and 7” x11” (17.8cm X 27.9cm) sign. Unit shall have Saf-T-Lok[®] arm assembly to swivel eyewash over sink. Unit shall be supplied with self-adjusting 2.4 gpm (9.1 lpm) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Eyewash heads with integral hinged covers to be manufactured of solvent resistant acetal mounted on a chrome plated brass wye. Eyewash covers are provided to inhibit dust and/or contamination when not in use. Eyewash units with deteriorating screens/filters are not acceptable.

***Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

MATERIALS OF CONSTRUCTION:

VALVE: ½” Chrome plated bronze stay open ball valve with chrome plated ball, stainless steel valve stem and stainless-steel push plate with actuation graphic.

PIPING: Polished chrome plated brass.

HEADS: Acetal dual stream heads with integral hinged covers and chrome plated brass wye assembly.

REGULATOR: Self-adjusting (2) 1.2 gpm (4.5 lpm) regulators.

SUPPLY: ½” NPT

WEIGHT: 4 lbs (1.841 kgs)

