



**ENCON SAFETY PRODUCTS FOR
NORTH, CENTRAL & SOUTH AMERICAS**

Arc Flash Clothing - 88/12

- Flame resistance guaranteed for the life of the garment.
- 12 and 40 cal/cm2 garments are available with access to higher protection upon request.
- Available in kits or individual parts
- Compliance Standards and Tests observed



Hearing Protection

Veratti® Cap Mount Earmuff



- High performance technology utilizes two layers of thick acoustic foam surrounding an additional interior sound block cup layer
- Tough ABS exterior cup shell
- Easily fits on most hard hats
- Soft premium foam seals the generous cup space for deluxe ear comfort
- NRR 25
- Certification: ANSI S3.19

Veratti® Deluxe Earmuff

- High performance technology utilizes two layers of thick acoustic foam surrounding an additional interior sound block cup layer
- Tough ABS exterior cup shell
- Self-adjusting, dual-material headband combines a soft, ventilated layer closest to the head with a structured and secure outer band
- NRR 28
- Certification: ANSI S3.19



Veratti® Folding Earmuff

- Quick and easy to fold and stow
- Sturdy and durable construction
- Generous space inside cup provides comfort with ear "breathability"
- NRR 23
- Certification: ANSI S3.19



Goggles

Veratti® 900™

- Soft TPR gasket provides full seal protection
- Premium AFR® coating provides superior fog resistance
- Protects against chemical splash, dust and flying particles and debris
- Low profile, snug and comfortable fit
- 3rd Party Certified to ANSI Z87.1:2020 (X), D3, CSA Z94.3:20



Veratti® M50™

- Wrap-around style provides excellent panoramic vision
- The soft, flexible PVC frame and the rotating strap hugs the face for a secure seal
- Built in ventilation channel provides extra fog control and cooling
- 3rd Party Certified to ANSI Z87.1:2020, D3, CSA Z94.3:20



Safety Spectacles

Veratti® Spectrum™

- Stylish look and comfort for all day wearability
- Full front and side protection
- Polarized version available with ENFOG® coating on the inside lens
- 3rd Party Certified to ANSI Z87.1:2020 (X) and CSA Z94.3:20



Veratti® Encounter™

- Available with ENFOG® and our Premium AFR® coating provides superior fog resistance
- Full TPR frame and integral nose piece for ultimate comfort and wearability.
- 5 point adjustable temple ratchet for a personalized fit
- Dielectric safety spectacle
- 3rd Party Certified to ANSI Z87.1:2020 (X) and CSA Z94.3:20



Veratti® Toretto™

- Universal fit nose bridge.
- 9.5 Base Curve Lens
- Ratchet angle-adjustable temples provide users with a personalized fit.
- Soft temple tip provides superior comfort.
- Economical price point
- 3rd Party Certified to ANSI Z87.1:2020 (X) and CSA Z94.3:20



Veratti® Primo™

- Provides protection against dust and airborne particles
- Elastic headband secures spectacle firmly and comfortably
- Ventilated, fire resistant PEVA foam insulation
- Premium AFR® coating provides superior fog resistance
- 3rd Party Certified to ANSI Z87.1:2020 (X), CSA Z94.3:20



Veratti® Lites 2.0™

- Adjustable temples
- Adjustable nose piece
- Brow guard protection
- Extremely light, weighs only 16 grams
- Premium AFR® coating provides superior fog resistance
- 3rd Party Certified to ANSI Z87.1:2020 (X) and CSA Z94.3:20



Veratti® Salvo™

- Ultra lightweight modern frame feels weightless, even on the longest of days
- Adjustable, soft nose pads provide maximum comfort and fit
- Ratcheting temples support fit flexibility.
- Available in Premium AFR®, Scratchcoat® and ENFOG® coated lenses
- 3rd Party Certified to ANSI Z87.1:2020



Veratti® Primo™ 2021

- Foam seal provides protection against airborne dust and particles
- Fire resistant elastic head band secures spectacle firmly
- Premium AFR® coating provides superior fog resistance
- 3rd Party Certified to ANSI Z87.1:2020 (X), CSA Z94.3:20



Veratti® Primo™ Plus

- Protection from dust and airborne particles
- Soft TPR inner frame provides extremem comfort and a secure fit
- Premium AFR® coating provides superior fog resistance
- 3rd Party Certified to ANSI Z87.1:2020 (X), CSA Z94.3:20

